# MEM 9937 SPORTSHIELD MOUNTING KIT SUZUKI MARAUDER **INSTRUCTIONS / PARTS LIST**

## **TOOLS REQUIRED: 3/16"** Allen wrench (provided)

- 1. Install the mounting plates onto the windshield using the pre-assembled bolts on the mounting plates. Use neoprene washers on both sides of the windshield. On each plate, get both tabs started before you tighten them. (see Figure 1.1 & 1.2) Note: \*(Wide) - Tabs point in towards each other.
- 2. Loosely install the four fork clamps on the forks, approximately 1.75 inches apart. (see Figure 2)

### INSTALL NOTE: THE INTERLOCKING PARTS SHOULD BE ON THE FRONT SIDE OF THE FORKS WHEN INSTALLED PROPERLY.

- **3.** Loosen the four mounting bolts that are to hold the mounting plates to the fork clamps, and slide the mounting plates onto the fork clamps. (see Figure 3)
- Adjust the height, angle, and alignment of the shield. Carefully check gas tank clearance, and tighten all 4. mounting bolts.
- 5. Make sure to check gas tank clearance and that no parts are rubbing before riding with the windshield.

WARNING: This is a quick disconnect kit. Always tighten down all mounting bolts after removing or installing the windshield every time.

Fig. 1.1 Left side plate



Fig. 1.2 Right side plate Fig. 2 fork clamps





Fig. 3 shows mounting of plates



#### Care and Cleaning Instructions

To clean your windshield, use only warm water and a mild non-abrasive, dishwashing liquid. Use a soft cloth, such as a T-shirt or flannel cloth. To protect your windshield, please use Novus #2 to remove minor scratches, or use a polish like Memphis Shades Shinola which is specially designed for plastic windshields; glass cleansing agents will cause severe damage to your windshield and will void your warranty.

Never use any glass products, petroleum based chemicals, or cleaning agents with ammonia, bleach or any

# MEM 9937 MOUNTING KIT MARAUDER SPORTSHIELD

PART #	DESCRIPTION	QTY.
M937	Mounting Instructions/Parts List	1
M1021	Left Mounting Plate	1
M1022	Right Mounting Plate	1
M504	Socket Shoulder Washer	4
S1115	Large Adjustable Clamp Assy. with 1/8" Spacer	4
M505	Button Nut	4
M543	Santoprene Grommet	4
M302	<sup>1</sup> / <sub>4</sub> " – 20 x <sup>1</sup> / <sub>2</sub> " SS Socket Head Cap Screw	4
M310	3/16" Short Arm Allen Wrench	1
M313	3/16" Allen Wrench Cover	1
M314	3/16" T-Handle Allen Wrench	1
M337	3/16" T-Handle Allen Wrench Cover	1

Memphis Shades warrants all product components, metal and plastic, against defects in materials and workmanship for 24 months.

## FOR PARTS AND WARRANTY HELP, CONTACT:

MEMPHIS SHADES P.O. Box 429 Rossville, TN 38066 (901) 853-0293

Visit us on the web at <u>www.memphisshades.com</u> or you can also reach us at customerservice@memphisshades.com